

SUPER BLASTOFF® MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBER: 1-800-424-9300

HEALTH HAZARD: 0 REACTIVITY: 0 FLAMMABILITY: 0 SPECIAL HAZARD: 0

SECTION I – PRODUCT IDENTIFICATION

TRADE NAME: SUPER BLAST OFF CLEANER

| | | |
|----------------------|--------|--------------------------|
| NSN 7930-01-381-3353 | SB-275 | 275 Gallon Container |
| NSN 7930-01-364-7375 | SB-1 | 55 Gallon Drum |
| NSN 7930-01-364-7376 | SB-2 | 5 Gallon Can |
| NSN 7930-01-363-2818 | SB-3 | 6/1 Gallon Per Box |
| NSN 7930-01-381-3398 | SB-32 | 12/1 Quart Per Box |
| NSN 7930-01-363-2819 | SB-24 | 12/24 oz Bottles Per Box |

SECTION II – INGREDIENTS

Contains: Surface active agents, palm oils, sequestering agents and other proprietary ingredients. None of which have hazardous ratings.

SECTION III – PHYSICAL DATA

| | |
|---|---|
| Boiling Point: (99.34° C) 215° F | Melting Point: N/A |
| Specific Gravity: (H ₂ O=1): 1.054 | Vapor Pressure: Near Water |
| Vapor Density: (Air=1): Near Water | Sol. in Water % by wt.: 100% |
| Volatiles By Volume: Near Water | Evaporation Rate: (H ₂ O=1): 1.124 |
| Appearance & Odor: Green & Pleasant | ph Value (10 G/L H ₂ O): 10.5 |

SECTION IV – FIRE AND EXPLOSION DATA

D.O.T. Class: 55
Flash Point: None (open cup test method)
Auto ignition: None
Flammable limits in air % by volume: 0 Lower: N/A Upper: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: N/A
Unusual Fire and Explosion Hazard: N/A

SECTION V – HEALTH HAZARD

Routes of Exposure

| | |
|------------------|---|
| Inhalation: | Negative |
| Skin Contact: | Negative |
| Skin Absorption: | Could be absorbed under extreme heat. |
| Eye Contact: | Irritant upon direct contact. |
| Ingestion: | Although non-toxic, Do Not Take Internally. Keep away from children. |

Affects of Overexposure

Acute Overexposure: None could be detected.
Chronic Overexposure: Will remove oil from skin.

Emergency and First Aid Procedures

Eyes: Remove contacts, Rinse with fresh water for 5 to 10 minutes.
Skin: Flush with water. Apply lotion or cream to replenish body oil.
Inhalation: N/A
Ingestion: Drink lots of water, lemon juice or milk
Note to Physician: If swallowed & irritation persists, induce vomiting.

SECTION VI SPECIAL PROTECTION INFORMATION

Specific Personal Protection Equipment

Respiratory (specific in detail): None required. What you are cleaning may give off fumes. If so take precautions by wearing mask.
Eye: Causes no more damage than soap in the eyes during bathing. However, try and not to spray into eyes. Product will irritate the eyes. Wear goggles.

Gloves: None needed unless operator has extremely sensitive skin. Wear OSHA approved gloves.

Other Clothing and Equipment: If spraying in strong wind use rubber apron or other protective clothing.

SECTION VII – SPILL OR LEAK PROCEDURES

Steps to be Taken if Material is Released or Spilled: Product is biodegradable. Flush with water & dispose of according to local, state, or federal laws. It is a violation of the law to discharge any product into rivers, streams or oceans.

SECTION VIII – REACTIVITY DATA

Conditions Contributing to Instability: Industrial bleaches or acids will neutralize this product.

Compatibility: With all products except industrial strength bleaches or acids.

Hazard's Decomposition Products: None

SECTION IX – SPECIAL PRECAUTIONS

Precautionary Statements: Do not mix with acids or bleaches as product will neutralize itself and may possibly give off toxic fumes.

Handling and Storage Requirements: Keep away from extreme heat. Do not puncture containers. Keep out of reach of children. Store in a safe, secure area.

This MSDS Prepared under the direction of:
DR. Talib Haq, , 916-381-4476

Prepared by: Earl L Smith

Manufacturer's Name: ELSCO International, 5690 Moorefield Drive, El Cajon, Ca, 92019, 1-888-84ELSCO, www.elscointl.net

Effective Date: 02 July 2007 **Revision:** N/A

Complies with current OSHA forms for MSDS also complies with GEMASSEG-RICHTLINIE 91-55 EWG, (EUROPEAN ECONOMIC COMMUNITY)
Prepared According to 29CFR 1910.1200

EMERGENCY TELEPHONE NUMBER: 1-800-424-9300